



**Brancotex Indústria Químicas Ltda.**

**OFFICE AND FACTORY:**

Road Dr. Círcero Borges de Moraes, 1615

Jd. California - Barueri | SP

Phone: +55 (11) 4199-5469

**vendas@brancotex.com.br**

## TECHNICAL BULLETIN

# BRANCOCRYL TEX PP 950

Vinyl copolymer in aqueous dispersion free of plasticizers.

### TECHNICAL CHARACTERISTICS:

|                  |             |
|------------------|-------------|
| Solids (%) ..... | 49,0 – 51,0 |
| Viscosity .....  | ≤ 100       |
| pH (100 %) ..... | 4,0 - 5,0   |

### APPLICATION:

**Brancocryl Tex PP 950** is an adhesive for the impregnation and coating system.

Binder of fibrous materials such as re-bonding of leather trimmings and defibred fabrics. Can also be used without fabric finishing. Application tips and adaptations of local key areas, application processes and evaluation, consult our technical department.

### STORAGE:

**Brancocryl Tex PP 950** must be protected from humid places, temperatures below 5°C should be stored in ventilated areas and never under sunlight.

Storage of the product must not exceed 6 months in its original packaging.

### PACKING:

The product **Brancocryl Tex PP 950** is packaged in 50kg barrels, 200kg tambours and 1000kg containers.

### Note:

The above statements are based on our tests and technical knowledge. They do not give legal guarantee regarding certain properties because many influences may occur during the handling and use of our products, not exempting the client from performing their own tests and controls.